

^{SINCE} 1950



FLAT

Specification

- Needle punched nonwoven textiles
- Finishing powdering

Use

- Lining of the trunk side walls
- Decorative layer under the back seats
- Hot-pressing of sandwiches

Products

• KARET RADHAUS 250 or 400, KARET RADHAUSE WR9 250 or 300, CARPET MACAN, ...

Material content

- 100 % PES or PP staple fibre
- BICO fibres
- LDPE and HDPE powder on the reverse side

WEIGHT	200 - 1200 g/m2 ±10%
COLOUR	On the basis of the required standard
MAXIMUM WIDTH	220 cm
MECHANICAL FINISHING	No
COATING	No
POWDERING	LDPE or HDPE powder
FORMATING	Rolls, formats or cuts
PACKAGING AND STORAGE	Rolls are packed in PE foil Formats and cuts are stored on a pallet and covered with PE foil Store in covered, dry and clean areas

Specific needs

• Other parameters of the product or changes of this product can be made by specifications of the purchase contract.

RETEX a.s., U nadrazi 894, 672 01 Moravsky Krumlov, Czech Republic, IN: 463 46 431, TIN: CZ46346431 The Company is registered by Regional Court in Brno, section B, entry 729. Tel.: +420 515 209 511 • info@retex.cz • www.retex.cz