



SINCE
1950

TADITIONAL QUALITY NONWOVENS

MALERVLIES

Nonwoven needle punched textile



Characteristic: Nonwoven textile mechanically bonded by needle punching and laminated by anti-slip transparent PE foil

Material content: 100 % Recycled fibres
PE foil, transparent, anti-slip, 20 - 25 g/m²
EVA binder

Colour: Various

Weight: 200 to 310 g/m²

Standard width: 1 or 2 m

Certification: Management system according to standards ISO 9001, ISO 14001, ISO 45001 and ISO 50001

Funktion:



PROTECTION



SEPARATION



ANTI-SLIP

Use:



PAINTING



MAINTENANCE



PACKAGING

Material specification sheet

Date: 01. 09. 2019

No: T-007-01



TRADITIONAL QUALITY NONWOVENS

Material specification sheet

Date: 01. 09. 2019

No: T-007-01

MALERVLIES

Nonwoven needle punched textile

MALERVLIES		230	250	270	300	310
PHYSICAL PROPERTIES						
Weight [±10 %] / EN 29073-1	g/m ²	230	250	270	300	310
Thickness / DIN 53855-3	mm	1,4	1,6	1,7	1,8	1,9
FUNCTION						
ANTI-SLIP		X	X	X	X	X
Protection	P	X	X	X	X	X
CHARACTERISTICS						
Description	Nonwoven textile mechanically bonded by needle punching and laminated by transperated anti-slip PE foil					
Material content	Recycled fibres PE foil, transparent, anti-slip, 20 - 25 g/m2 EVA binder					
Colour	Various					
DIMENSION, PACKAGING AND STORAGE						
Roll width	m	1 or 2	1 or 2	1 or 2	1 or 2	1 or 2
Roll lenght	m	10, 25 or 50	25 or 50	25 or 50	25 or 50	25 or 50
Packaging	Rolls are packed in PE foil.					
Storage	In covered, clean and dry spaces					

The above technical parameters are average values and serve for general information. The manufacturer reserves the right to change it.